

Network Video Recorder

GT-NR401/801/1601



- 4/8/16-ch HD video input
- 1 SATA max to 3 TB
- H.264 compression
- With VGA and HDMI output
- Support controlling PTZ via mouse
- Support Mobile view (IOS, Android)
- Support Multi-language
- Support IE web server, client software, CMS software
- Support DDNS DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL etc.

GT-NR3208



- 32-ch HD video input
- 8 SATA max to 24 TB
- H.264 compression
- Support TV, VGA, HDMI output
- Support controlling PTZ via mouse
- Support Mobile view (IOS, Android)
- Support Multi-language
- Support IE web server, client software, CMS software
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, IP searching etc.

GT-NR1602



- 16-ch HD video input
- With 2 SATAS, totally support 6TB
- H.264 compression
- Support TV, VGA, HDMI output
- Support mobile view (IOS, Android)
- Support Multi-language
- Support IE web server, client software, CMS software
- Support DHCP, DNS, DDNS, EMAIL, IP search etc.

GT-NR3204



- 32-ch HD video input
- 4 SATA max to 12 TB
- H.264 compression
- Support TV, VGA, HDMI output
- Support controlling PTZ via mouse
- Support Mobile view (IOS, Android)
- Support Multi-language
- Support IE web server, client software, CMS software
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, IP searching

Digital Video Recorder

GT-ADR401M/801M



- 4/8 ch video input
- Supports hybrid video input – AHD, Analog and IP camera
- With VGA, HDMI HD output
- H.264 compression
- Supports phone monitoring (iPhone, Android)
- With 1 SATA, max to 3 TB
- Supports web browser access
- Support Multi-language
- Support IE web server, client software

GT-ADR1601M



- 16-ch video input
- Supports hybrid video input – AHD, Analog and IP camera
- With VGA, HDMI HD output
- H.264 compression
- Supports phone monitoring (iPhone, Android)
- With 1 SATA, max to 3 TB
- Supports web browser access
- Support Multi-language
- Support IE web server, client software

About ZKAccess

ZKAccess is a leading provider of biometric and RFID solutions. Product offerings include Access Control readers and panels, Near & Long range Facial Recognition Cameras, Elevator access controllers, IP and AHD (analog high definition) cameras, Turnstiles and Consumer products including fingerprint-based battery-operated Biometric Door Locks. ZKAccess solutions are multi-lingual and localized in over 18 different languages. ZKAccess designs specialized products for specific markets and provides local customer support to its North American customers. Our U.S. facility includes a large global showroom and warehouse. Based in Fairfield, NJ, ZKAccess is a division of ZKTeco, a leading global developer of security and time management solutions. ZKAccess is synonymous with technical innovation, quality, speed-to-market and reliability.

ZKAccess[®]
Advanced Solutions, Total Security

Why ZKTeco?

- ZKTeco is one of the largest global manufacturers and distributors of biometric & RFID security solutions.
- We've sold over 15 million units which are supported by more than 14 global offices.
- We build all of our products in-house at our state-of-the-art 700,000 square foot ISO 9001 certified factory.
- We control everything - from R&D, manufacturing, product design, terminal assembly and logistics/shipping
- Our huge economies of scale allow us to pass our significant savings on to our customers.
- We're flexible, reputable, easy to work with and we have offices all around the globe ready to serve you.







ZKAccess

6 Kingsbridge Road, Unit 8, Fairfield, NJ 07004
Phone: (862) 505-2101 • Fax: (862) 204-5906
sales@zkaccess.com • www.zkaccess.com

ZKAccess - division of ZKTeco

**Flexible and
Affordable
IP-Based & AHD
Surveillance
Cameras**

	IP Camera	IP Camera	IP Camera	IP Camera	IP Camera	IP Camera	IP Camera	IP Camera
Picture								
Model	GT-BB510/513/520	GT-BC510/513/520	GT-BD510/513/520	GT-BE510/513/520	GT-BF510/513/520	GT-BG510/513/520	GT-DA510/513/520	GT-DB510/513/520
Image Sensor	OV9712/ Aptina 130	OV9712/Aptina 130/	OV9712/Aptina 130/	OV9712/Aptina 130/	OV9712/Aptina 130/	OV9712/Aptina 130/	OV9712/Aptina 130/	OV9712/Aptina 130/
	SONY 122	SONY 122	SONY 122	SONY 122	SONY 122	SONY 122	SONY 122	SONY 122
Lens	3.6mm	2.8–12mm Varifocal	3.6mm	3.6mm	3.6mm	6mm	3.6mm	2.8–12mm Varifocal
Max Resolution	720P/960P/1080P	720P/960P/1080P	720P/960P/1080P	720P/960P/1080P	720P/960P/1080P	720P/960P/1080P	720P/960P/1080P	720P/960P/1080P
Sensitivity	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux
IR Distance	15m	25m	10m	15m	15m	10m	10m	10m
Infrared Filter	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT
Protection Rating	IP65	IP65	IP65	N/A	IP65	IP65	IP65	N/A
Operating Temp	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C
Image Compression	H.264	H.264	H.264	H.264	H.264	H.264	H.264	H.264
Web Server	YES	YES	YES	YES	YES	YES	YES	YES
POE	Optional built-in POE	Optional built-in POE	Optional external POE	Optional external POE	Optional built-in POE	Optional built-in POE	Optional external POE	Optional external POE
	IP Camera	IP Camera	IP Camera	IP Camera	AHD Camera	AHD Camera	AHD Camera	AHD Camera

	IP Camera	IP Camera	IP Camera	IP Camera	AHD Camera	AHD Camera	AHD Camera	AHD Camera
Picture								
Model	GT-DC510/513/520	GT-DD510/513/520	GT-SD552	GT-SD652/682	GT-ADA210/213	GT-ADB210/213	GT-ADC210/213	GT-ADD210/213
Image Sensor	OV9712/Aptina 130/	OV9712/Aptina 130/	1/3" APTINA CMOS	1/3" low-light CMOS	AHD 2431+OV9712	AHD 2431+OV9712	AHD 2431+OV9712	AHD 2431+OV9712
	SONY 122	SONY 122	---	1/2.8" CMOS Exmor	Sony IMX238	Sony IMX238	Sony IMX238	Sony IMX238
Lens	3.6mm	2.8–12mm Varifocal	10X optical zoom	18X optical zoom	3.6mm	3.6mm	3.6mm	3.6mm
Max Resolution	720P/960P/1080P	720P/960P/1080P	1.3 Megapixel	1.3MP / 2.0MP	1.0MP / 1.3MP	1.0MP / 1.3MP	1.0MP / 1.3MP	1.0MP / 1.3MP
Sensitivity	IR on: 0Lux	IR on: 0Lux	IR on: 0.01Lux	IR on: 0.01Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux
IR Distance	10m	10m	50m	100m	10m	10m	10m	10m
Infrared Filter	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT
Protection Rating	N/A	N/A	IP65	IP65	N/A	N/A	N/A	N/A
Operating Temp	-10°C~+50°C	-10°C~+50°C	-10°C~+65°C	-30°C~+65°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C
Image Compression	N/A	H.264	H.264	H.264	H.264	H.264	H.264	H.264
Web Server	YES	YES	YES	YES	YES	YES	YES	YES
POE	Optional external POE	Optional external POE	N/A	N/A	Optional external POE	Optional built-in POE	Optional external POE	Optional external POE
	AHD Camera	AHD Camera	AHD Camera	AHD Camera	AHD Camera	AHD Camera	AHD Camera	AHD Camera

	IP Camera	IP Camera	IP Camera	IP Camera	IP Camera	IP Camera	IP Camera	IP Camera
Picture								
Model	GT-ADE210/213	GT-ADF210/213	GT-ADG210/213	GT-ADH210/213	GT-ADI210/213	GT-ADK210/213	GT-ADO210/213	GT-ADP210/213
Image Sensor	AHD 2431+OV9712	AHD 2431+OV9712	AHD 2431+OV9712	AHD 2431+OV9712	AHD 2431+OV9712	AHD 2431+OV9712	AHD 2431+OV9712	AHD 2431+OV9712
	Sony IMX238	Sony IMX238	Sony IMX238	Sony IMX238	Sony IMX238	Sony IMX238	Sony IMX238	Sony IMX238
Lens	3.6mm	3.6mm	3.6mm	3.6mm	2.8MM-12MM	2.8MM-12MM	3.6mm	3.6mm
Max Resolution	1.0MP / 1.3MP	1.0MP / 1.3MP	1.0MP / 1.3MP	1.0MP / 1.3MP	1.0MP / 1.3MP	1.0MP / 1.3MP	1.0MP / 1.3MP	1.0MP / 1.3MP
Sensitivity	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux	IR on: 0Lux
IR Distance	10m	10m	10m	10m	10m	10m	25m	15m
Infrared Filter	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT	IR-CUT
Protection Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Operating Temp	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C
Image Compression	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Web Server	YES	YES	YES	YES	YES	YES	YES	YES
POE	Optional external POE	Optional external POE	Optional external POE	Optional external POE	Optional external POE	Optional built-in POE	Optional external POE	Optional external POE